


Hazardous Area Equipment

Syrex Exd Buzzer



Features

- Rated for Category 2 use (formerly Zone 1 & 2)
- ATEX approved
-  II 2 G EExd e IIC T6
- Heavy duty buzzer
- Weatherproof to IP66
- Rugged construction

Overview

The Exd Buzzer is an explosion proof buzzer designed for use in hazardous areas where a distinctive signal is required. Certified to ATEX II2G EExd e IIC T6, it is suitable for use in Zone 1 and Zone 2 areas.


Producing a tone with low frequency, it cuts through background noise more effectively than many other devices of a similar output.

Mounted in a rugged reinforced polyester case and weatherproof to IP66, it is suitable for use in the most arduous conditions.

- Fire
- Railway/Marine
- Security
- Hazardous Area
- Industrial
- Public Warning

Applications

- General signalling; evacuation and process control alarm



Part No.	Colours	Audibility at 1m	Tones	Voltage	Current
17-970220	Black	Up to 105dB (A)	1	230V AC 50Hz	70mA
17-970235	Black	Up to 105dB (A)	1	110V AC 50Hz	150mA
17-970236	Black	Up to 105dB (A)	1	24V DC	650mA

IP Rating: IP66 Rating: Continuous Frequency: 1000Hz Operating Temp: -20°C to +40°C
 Construction: Glass Fibre Reinforced Polyester Cable Entries: 1 Weight: 3.5kg